

GLADIATOR DP 5W-40

**PREMIUM FULLY SYNTHETIC
DOUBLE PROTECTION
PETROL ENGINE OIL**

BULWARK GLADIATOR DP oils are multi-grade premium fully synthetic motor oils of the latest generation suitable for use in modern engines of passenger cars, light commercial trucks, sport cars and vans including turbocharged and supercharged engines. They provide best in class wear protection and all-round superior performance.

BULWARK GLADIATOR DP 5W-40 oil is formulated using premium quality synthetic base oils and advanced high-performance additive packages. Recommended for use during all-season operations in gasoline engines of cars from European, American, Japanese and other Asian manufacturers, which require oils with API SN, ACEA A3/B4 performance levels and SAE 5W-40 viscosity.

PERFORMANCE LEVEL*

- API SN
- ACEA A3/B4
- MB 229.3, 229.5
- PORSCHE A40; VW 502.00/505.00;
- BMW LL-01
- RN 0700/0710
- PSA B71 2296

KEY BENEFITS

- Excellent anti-oxidation & anti-corrosion properties provide protection to the engine against wear in severe operating conditions.
- Unique formulation minimizes oil consumption.
- Facilitates smoother engine operation at high loads and in "start-stop" mode.
- Easy cold start and excellent low-temperature properties, reduces engine start-up wear.
- Prevents the formation of high and low temperature deposits on the engine components.
- High BN reserve and retention allow use of high sulfur fuel.

TYPICAL CHARACTERISTICS**

Properties	Test Methods	5W-40
Density @ 29.5°C, Kg/m3	ASTM D4052	0.857
Kinematic Viscosity @ 100°C cSt	ASTM D7042	13.78
Viscosity Index	ASTM D2270	166
Cold Cranking Viscosity at -30°C, mPa-s	ASTM D5293	5060
Borderline Pumping Viscosity at -35°C, mPa-s	ASTM D4684	18,520
Sulphated Ash, %	ASTM D874	0.82
Flash Point, COC, °C	ASTM D92	242
Foam Stability	ASTM D892	
Seq I		0/0
Seq II		0/0
Seq III		0/0
Pour Point, °C	ASTM D97	-48
Total Base Number, mg KOH/g	ASTM D2896B	8.60

* Performance levels indicated may include licensed API specs or specs that our products meet or exceed

** Typical Characteristics are typical values. Minor variations within the permissible tolerance limits may be expected on the final product.

STORAGE

All packages should be stored under cover. Where outside storage is unavoidable, drums should be laid horizontally to avoid the possible ingress of water and the obliteration of drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either Bulwark International UK Ltd or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. Please consult our local representative if you require any further information.

Bulwark International UK Ltd, 34 Woodland Road, Sawston, CB22 3DU, United Kingdom. info@bulwarkauto.co.uk